



Brew Tubing



Fluid Transfer Solutions for Every Step of the Brewing Process



Low Temperature Applications

Perfect for Brewing and Draft Beer Dispensing

Superthane® - The ultimate PVC-free beer transfer tubing with barrier properties

- -85°F to 175°F
- 22 to 135 psi*
- Free of phthalates
- Non-toxic ingredients conform to FDA standards
- 1/16" to 2" I.D.
- NSF-61 listed

Clearflo® - Glass-like clarity in a lightweight, flexible tube lets you see the beer

- -41°F to 175°F
- 14 to 70 psi*
- Non-toxic ingredients conform to FDA standards
- 1/16" to 4" I.D.
- NSF-51 listed

Clearflo Ag-47 - Antimicrobial properties guard against beer spoilers

- -40°F to 125°F
- 37 to 236 psi*
- Free of phthalates
- Non-toxic ingredients conform to FDA standards
- 1/8" to 1" I.D.
- NSF-51 listed

Nylonbrade® - Reinforced for pressure applications such as CO2 and nitrogen transfer, plus chiller transfer and blowoff

- -50°F to 140°F
- 50 to 465 psi*
- Non-toxic ingredients conform to FDA standards
- 1/8" to 2" I.D.
- NSF-51 listed

High Temperature Applications

Perfect for Mash Vessel, Brew Kettle and Hot Liquor Tank

Silcon® - Reusable – withstands repeated sterilization

- -100°F to 350°F
- 5 to 28 psi*
- Good for fermentation and where purity is essential
- 1/16" to 3/4" I.D.
- NSF-51 listed

Silbrade® - Braid reinforced for higher pressure uses

- -99°F to 350°F
- 75 to 233 psi*
- Handles higher pressures than unreinforced tubing
- Platinum cured version available
- 1/8" to 1" I.D.
- NSF-51 listed

*Dependent on size



About BrewSavor®



BrewSavor is a brand established by NewAge® Industries, an employee-owned company in business since 1954. Our Brew Crew is dedicated to manufacturing innovative fluid transfer tubing and hose products that exceed expectations of both craft brewers and home brewers alike.

We are equally committed to sustainability and have taken significant steps towards becoming a green company with our roof top solar array and numerous other green initiatives.

BrewSavor is devoted to quality and we understand the importance of flavor consistency when it comes to your brew.

Let us help you taste your vision.

Other BrewSavor Fluid Transfer Options



Crush Resistant Reinforced Brewery Hose

- Assembled and ready to ship in 10', 20', 25' and 50' lengths
- Rebounds to original shape after impact



Kink Resistant Reinforced Brewery Hose

- Tighter bend radius; more resistant to kinking
- Ideal for suction and discharge applications

Committed To Sustainability

To learn more about our green initiatives, download our sustainability brochure at www.brewsavor.com.



ESOP Employee Owned
for Your Benefit



145 James Way
Southampton, PA 18966
www.brewsavor.com

Phone: 888-777-0147
215-526-2300
Fax: 800-837-1856
215-526-2190
info@brewsavor.com

© NewAge Industries, Inc. 2019

BrewSavor, Superthane, Clearflo, Nylobrade, Silbrade, Silcon, NewAge and "Taste Your Vision" are registered trademarks of NewAge® Industries, Inc. NOTICE: NewAge Industries, Inc. has been a privately owned corporation since 1954. Neither the corporation nor its principals are affiliated, in any way, with any other group or entity either representing themselves as or being referred to by the term New-Age.

WARRANTY: NewAge Industries' products are warranted to be free from defects in material and workmanship. Any product found to carry such defects will be replaced without charge. This warranty is limited only to the replacement of NewAge Industries' products, item for item, which after examination by NewAge Industries are deemed defective. NewAge Industries specifically disclaims any other liability. The data supplied is provided as a helpful guideline and is believed to be reliable; however, nothing stated shall constitute a guarantee, recommendation, or warranty for any application.

© NewAge Industries, Inc. 2019 Specifications are subject to change without notice.

8/23/19